

Controlled Air Design
(800) 635-0298




DF 22



Depureco Industrial Vacuums USA


19121 Marketplace Avenue, Building 1, Suite 165
Plum Creek Business Park • Kyle • TX 78640

www.depurecousa.com
info@depurecousa.com

3 HP

POWER

3720.01 in²

FILTER

17/26 gal Bin

CAPACITY

ELECTRICAL FAN

480V
Max Airflow= 265 | 589 | 753 CFM

STAR FILTER

 3720.01 in²

**MANUAL SHAKER
CLEANING SYSTEM**

Smart handle for shaking
the filter aggressively to
release dust.

DETACHABLE CONTAINER




17/26 gal



SPEC SHEET

	Units	DF 22
Motors Type		Fan
Power	HP	3
Voltage Frequency	V Hz	480/60
Maximum vacuum	inH2O	25.9
Maximum air flow	CFM	256 589 753
Inlet	Ø in	3.94 4.72 5.90
Noise level - (EN ISO 3744)	dB(A)	73
Bin capacity	gal	17/26
Dimensions	in	25.98 X 31.50
Height	in	64
Weight	lb	264
Primary filter		
Type		Star
Surface area Diameter (Class EN 60335-2-69)	in ² in	3720.01 M Class
Media		Polyester
Filter cleaning		Manual
Absolute filter (optional)		
Surface area (Class - EN 1822)	in ²	18.600 H13
Media		Fiberglass


OPTIONAL FILTERS



ANT M
Antistatic filter



PTFE
PTFE filter



PTFE ANT
Antistatic PTFE filter



NOMEX
For High temperatures



H13
HEPA secondary filter

OPTIONAL



GRD
Grounding



BX
AISI 304 stainless steel bin



26 GAL
Bin with 26 gal capacity

ACCESSORIES



FLANGED CONE CONNECTION